

**PREFERRED SUPPLIERS TO PILBARA IRON
IN 28 OF THEIR WORKSHOPS**

**100's
SOLD**

Just leave THE DIRTY WORK TO

Why waste time & money
washing parts by hand or
renting a parts washer,
when you can buy a quality
Hotwash system
for under \$22 per day!

hotwash
AUSTRALIA PTY LTD

“ALL NEW, HEAVY DUTY RANGE”

To manually wash parts for 1 hour a day can cost up to \$750 per month or \$10,000pa for labour alone.

Purchase your own Hotwash Parts Degreaser from as little as \$75 per week giving you a potential saving of around \$10,000pa!

Plus you'll free up 250 staff hours pa to spend on income producing duties.

So when it comes to getting the very best ROI for your business, it makes sense to purchase a quality Hotwash system today.

- New! Optional gear driven turntable for operator safety.
- New! Auto solenoid water top up system. Easy maintenance.
- New! Fast waste water pump out for quick servicing.
- New! Complies with ISO AS4024 machine safe standards.
- New! Mine site spec IP65 dust and moisture electrical cabinet.
- New! Heavy duty basket construction for greater durability.
- New! 24-7 digital time clock for auto turn on/off.
- New! Laser cut fabrication for precision manufacture.



the clean technology

Hotwash, 'cleaning up' industry for over 20 years

the quality selection

The centrifugal action of the rotating basket with the force & volume of hot water and biodegradable detergent spraying from jets surrounding the basket ensures fast and efficient cleaning & drying of components... All without wasting valuable productive work time or staff.

The special detergent contains a rust inhibitor which protects all metal surfaces and rust proofs the inside of the machine and component parts, giving many years of trouble-free service.

The water used in the washing cycle is contained in a closed system within the machine and is constantly recycled which ensures low running costs and maximum use and efficiency of the detergent. The water is quickly heated to operating temperature by an immersed element, using 3 phase power for maximum efficiency.

The wash cycle is controlled by a timing device and the water temperature is automatically maintained by a temperature controller. Power consumption is kept minimal by an insulated tank.

So a Hotwash system will save you time and money!

a range of uses...

- Agricultural • Auto Electrical
- Automatic Transmissions • Automotive
- Auto Part Recyclers • Aviation Brake & Clutch • Cylinder Heads • Diesel Engines • Electrical • Electroplating
- Engine Reconditioning • Fuel Injection
- Gear Boxes • Maintenance
- Manufacturing • Marine
- Mining • Motor Cycles
- Power Stations • Railways
- and materials cleaned...
- Steel • Aluminium • Cast Iron
- Brass • Plastics



HW800



HW1100G



HW1600HD




AGITATING TANKS

specifications

MODEL	HW800	HW1100	HW1400
Gear Driven Basket	Optional	Optional	Optional
Basket Diameter (mm)	800	1100	1400
Working Height (mm)	420	550	700
MACHINE DIMENSIONS:			
Height (Lid closed)	1030	1205	1520
Width	1090	1400	1950
Depth	970	1290	1780
Pump Motor (kW)	2.2	4	5.5
Tank Capacity (Ltrs)	125	275	400
Voltage (1PH or 3PH)	3PH	3PH	3PH
Heating Elements	3 x 1.8 KW	3 x 2.4 KW	3 x 3 KW
Connection	20amp, 4Pin	20amp, 4Pin	32amp, 4Pin
Cycle Timer	Yes	Yes	Yes
Insulation	Yes	Yes	Yes
Stainless Steel Construction	Optional	Optional	Optional

Options include: Small parts baskets, optional pump size, detergent. Specifications may be modified at any time due to technical development. *Calculations are based on purchase of Model HW600 and are subject to change without notice.



hotwash
AUSTRALIA PTY LTD

FREECALL 1800 644 378
FREE FAX 1800 645 110
E: info@hotwash.com.au
W: www.hotwash.com.au

DISTRIBUTED BY: