ALLRIG – High Pressure Truck Wash

Exterior Vehicle Cleaning Detergent and Traffic Film Remover

Product Description

ALLRIG – High Pressure Truck Wash is a concentrated biodegradable, water based, high performance detergent, specifically formulated for the exterior cleaning of all vehicle surfaces. It is unique in that it will remove traffic film without the need for physical agitation.

Features and Benefits

- Biodegradable
- Does not contain harsh caustic compounds or solvents
- Free rinsing properties reduces water consumption
- Added corrosion inhibitors to help protect steel and aluminium
- Eliminates static build up on paint work helping to reduce subsequent dirt pick-up
- Suitable for use in hard water areas
- Safe on all vehicles surfaces including aluminium, steel, galvanised, paint, glass and plastic.
- Classified as non hazardous to the criteria of NOHSC
- Not classified as dangerous for the purpose of transport and storage
- Economical

Properties

- Appearance – clear blue liquid
- SG – 1.05
- Flash point – none
- Odour – odourless

Method of Use

Optimum cleaning performance is achieved by foam spraying the entire vehicle from the bottom up and leaving for approximately 5 minutes. This should be followed by pressure rinsing from the bottom up using a high pressure cleaning machine with a minimum nozzle pressure of 3,500kpa (500psi). The nozzle should be held at about 15 to 30 centimetres from the vehicle surface.

Normally **ALLRIG – High Pressure Truck Wash** is used at a dilution of 2% to 3% although higher concentrations can be employed for particularly difficult applications.

Solution Control

1. Take a 100 ml sample into a flask
2. Add 5 drops of Bromo-Cresol Green (BCG) indicator
3. Titrate with 0.1 N Acid to a yellow endpoint
4. Strength in % = mls used x 0.19

Packaging

ALLRIG – High Pressure Truck Wash is available in 20 litre drums.

Safety, Transport and Storage Information

Please refer to the Material Safety Data Sheet.

Issue Date: December 2012